

BRASSCHECK VALVE



BRASS CHECK VALVE




BRASS SPRING CHECK VALVE PG-SV-690



Technical Specification

1. Normal pressure: 25 bar
2. Working medium: water
3. Working temperature: $0\text{ }^{\circ}\text{C} \leq t \leq 100\text{ }^{\circ}\text{C}$
4. Thread standard: ISO 228-1:2000
5. Surface finish: Sanding polishing



Material Specification


ITEM	PARTS	MATERIAL	SIZE	APPROX.W(gm)	1/2"	1"
1	Body	Brass	1/2"	130	18	180
2	Spring	Stainless Steel	3/4"	205	14	140
3	Stem	Brass	1"	300	8	80
4	O-Ring	Silicon	1 1/4"	380	5	50
5	Bonnet	Brass	1 1/2"	700	5	50
			2"	1080	1	30

BRASS SPRING CHECK VALVE PG-SV-601 PLUS



Technical Specification

1. Normal pressure: 25 bar
2. Working medium: water
3. Working temperature: $0\text{ }^{\circ}\text{C} \leq t \leq 100\text{ }^{\circ}\text{C}$
4. Thread standard: ISO 228-1:2000
5. Surface finish: Sanding polishing



Material Specification


ITEM	PARTS	MATERIAL	SIZE	APPROX.W(gm)	1/2"	1"
1	Body	Brass	3/4"	180	14	140
2	Spring	Stainless Steel	1"	250	8	80
3	Stem	Brass	1 1/2"	570	5	50
4	O-Ring	Silicon				
5	Bonnet	Brass				

BRASS SWING CHECK VALVE PG-SW-650



Technical Specification

1. Normal pressure: 25 bar
2. Working medium: water
3. Working temperature: $0\text{ }^{\circ}\text{C} \leq t \leq 100\text{ }^{\circ}\text{C}$
4. Thread standard: ISO 228-1:2000
5. Surface finish: Sanding



Material Specification


ITEM	PARTS	MATERIAL	SIZE	APPROX.W(gm)	1/2"	1"
1	Bonnet	Brass	1/2"	110	20	200
2	Body	Brass	3/4"	190	12	120
3	Screw	Brass	1"	310	8	80
4	Gate	Brass	1 1/4"	450	4	40
			1 1/2"	570	4	40

BRASS Y-STRAINER VALVE PG-SVFT-510



Technical Specification

1. Normal pressure: 25 bar
2. Working medium: water
3. Working temperature: $0\text{ }^{\circ}\text{C} \leq t \leq 100\text{ }^{\circ}\text{C}$
4. Thread standard: ISO 228-1:2000
5. Surface finish: Polished & Chromed



Material Specification

ITEM	PARTS	MATERIAL	SIZE	APPROX.W(gm)	1/2"	1"
1	Bonnet	Brass	1/2"	125	12	120
2	Filter	Stainless Steel	3/4"	220	10	100
3	Body	Brass	1"	345	6	60
			1 1/4"	510	4	40
			1 1/2"	750	2	20
			2"	1280	2	20



BRASS CHECK VALVE




BRASS FOOT VALVE PG-FTV-630



Technical Specification

- 1.Normal pressure: 25 bar
- 2.Working medium: water
- 3.Working Temperature: 0 °C ≤ t ≤ 100 °C
- 4.Thread standard: ISO 228-1:2000
- 5.Surface finish:Sanding Polishing



Material Specification


ITEM	PARTS	MATERIAL	SIZE	APPROX.W(gm)	⊕	⊖
1	Strainer	Brass	3/4"	190	12	120
2	O-Ring	NBR	1"	260	8	80
3	Stem Disc	Brass	1 1/4"	380	4	40
4	Body	Brass	1 1/2"	460	3	30

BRASS SAFETY CHECK VALVE PG-SFV-701



Technical Specification

- 1.Calibration pressure: 8±0.5bar
- 2.Working medium: water
- 3.Working Temperature: 0 °C ≤ t ≤ 100 °C
- 4.Thread standard: ISO 228 1:2000
- 5.Surface finish:Sanding polishing & Chromed



Material Specification

ITEM	PARTS	MATERIAL	SIZE	APPROX.W(gm)	⊕	⊖
1	Body	Brass	1/2"	72	20	200
2	Cover	Plastic				
3	Level Nut	Plastic				
4	Spring	Stainless Steel				
5	Barrier	Plastic				
6	Spring	Stainless Steel				
7	Stem	Brass				
8	Core	Brass				

CHECK VALVE FILTER PG-910-FILTER



Technical Specification

1. Working medium: water
- 2.Working Temperature: 0 °C ≤ t ≤ 100 °C
- 3.Surface finish: Stainless Steel
- 4.Material standard 304

Material Specification

G	⊕
1/2"	240
3/4"	200
1"	200
1 1/4"	110
1 1/2"	100
2"	120
2 1/2"	100
3"	60
4"	40

